

with a splined tang for anchoring in the sealant filled mortar joint; manufactured in a selection of sizes, and in continuous strips for field cutting and fitting.

1.03 SUBMITTALS

- A. **Manufacturers' information, shop drawings (manufacturer's standard detail sheets), materials lists and certificates for the products proposed for use.**
- B. **Samples: 12" long pieces of each type of stone flashing proposed for use.**

1.04 QUALITY ASSURANCE

- A. **Restoration Specialist: Work must be performed by a firm having not less than 5 years successful experience in comparable masonry restoration projects and employing personnel skilled in the restoration processes and operations indicated.**

1.05 WARRANTY

- A. **Provide copies of all manufacturer's guarantees of materials and installation, duly signed and dated.**
- B. **Include all warranty inspections by a manufacturer's representative necessary to effect the guarantee of material performance and its installation.**

PART 2---PRODUCTS

2.01 MANUFACTURERS

- A. **Weathercap, Inc.
P.O. Box 1776
Slidell, LA 70459-1776
504/649-4000**

2.02 MATERIALS

- A. **Tee Caps: Lead Stone Flashing strips (Weathercap, Inc.), or approved equal.**
 - 1. **Use size of strips as recommended by sealant manufacturer and compatible with style and configuration of existing.**
 - 2. **Strips should be of sufficient size to cover the joint width, plus a percentage allowance for anticipated joint movement, plus 1/4".**
- B. **Sealant: As recommended by Tee Cap manufacturer. See also 07900-01-S for guidance. Test to make sure sealant does not stain masonry.**

2.03 EQUIPMENT

- A. **1" masking tape**